



Product Data Sheet

4107650311GS-P

Swivel castor 75 mm with plate fixing 60x60 mm, TPE-tyre. 44 pce/box.

Housing made of zinc plated, pressed steel with double ball race swivel head with mounted plate fixing 60x60 mm, riveted wheel axle.
Wheel with plain bearing and grey TPE tyre RAL 7001, hub in black PP, and fitted with small plastic thread-guards to protect the greased plain bearing.

Technical specification

Wheel diameter (mm)	75
Width of tread (mm)	24
Offset (mm)	35
Swivel radius (mm)	72,5
Size of plate (mm)	60x60
CC distance (mm)	46x46
Overall height (mm)	99
Dynamic load capacity (kg)	55
Static load capacity (kg)	110
Hardness of tread (shore)	85° Shore A
Test method standard	EN 12530
Temperature area C°	-20°C to +50°C
Net weight kg	0,29
Environmental status	RoHS (EU) - Approved
Hole diameter, plate (mm)	8,5x6,5
Wheel attachment	Top plate
Diameter centre bolt hole (mm)	..
Castor model (brake)
Hole diameter loose wheel (mm)
Tread width, loose wheel (mm)	..
Wheel bearingPlain bearing
Article number, EAN7340101226941
Statistic number83022090
Qty/box 44,00

