



## Product Data Sheet

# 4110650311GS-P

**Swivel castor 100 mm with plate fixing 60x60 mm, TPE-tyre.  
36 pce/box.**

Housing made of zinc-chromatized pressed steel with double ball race swivel head with mounted plate, riveted wheel axle.

Wheel with plain bearing and have TPE tyre RAL 7001, hub in black PP and fitted with small thread-guards.

### Technical specification

Wheel diameter (mm)	100
Width of tread (mm)	24
Offset (mm)	35
Swivel radius (mm)	85
Size of plate (mm)	60x60
CC distance (mm)	46x46
Overall height (mm)	121
Dynamic load capacity (kg)	55
Static load capacity (kg)	110
Hardness of tread (shore)	85° Shore A
Test method standard	EN 12530
Temperature area C°	-20°C to +50°C
Net weight kg	0,34
Environmental status	RoHS (EU) - Approved
Hole diameter, plate (mm)	8,5x6,5
Wheel attachment	Top plate
Diameter centre bolt hole (mm)	..
Castor model (brake)	.....
Hole diameter loose wheel (mm)	.....
Tread width, loose wheel (mm)	..
Wheel bearing	.....Plain bearing
Article number, EAN	.....7340101226958
Statistic number	.....83022090
Qty/box	.....36,00

